



SIRJAN GOSTAR CO.

Date: October 2012 Wed 10
No: 91/SGC/2152

PVC Resin

TYPE	S-57	S-60	S-65	S-67	S-70
Appearance	W.P.*	W.P.	W.P.	W.P.	W.P.
Inherent Viscosity	0.67-0.72	0.74-0.79	0.85-0.91	0.91-0.95	0.98-1.02
K-Value	56-58	59-61	64-66	66-68	69-71
Particle Size	Nil	Nil	Nil	Nil	Nil
%Retained on 40 Mesh	= > 85	= > 85	= > 85	= > 85	= > 85
%Retained on 200 Mesh					
Porosity [ML/GR]	0.05-0.2	0.05-0.22	0.1-0.26	0.12-0.28	0.2-0.32
Volatile Matter [Heart Loss]%Max	0.7	0.7	0.7	0.7	0.7
Bulk Density [GR/CC]	0.5-0.62	0.55-0.61	0.46-0.60	0.45-0.57	0.44-0.5
Dark Resin [Per 10 SQ.IN.]	0-10	0-10	0-10		0-10

Packing: 25 Kg PE bags and big bags 1250 Kg.

CAUSTIC SODA [liquid]

DESC	RANGE	UNIT
NAOH	45-50	% WT
NACL	50MAX	PPM
NA2CO3	0.1	%WT
HG	0.3MAX	PPM

Packing: Bulk.