



SIRJAN GOSTAR CO.

Product Data and Technical Information



POLYMER TYPE: POLYPROPYLENE HOMOPOLYMER



GRADE NAME : RG 1128 MC



PACKING : PP bags of 25 kgs, 50 bags on a pallet shrieked by PE



APPLICATION : Cast films with high slip behavior for all kind of packaging and stationary films



PRODUCT FEATURES : Homopolymer contains antiblocking and slip agents with high stiffness



PROCESSING METHOD : Extrusion

Property	Test Method	Unit	Value
MFR (230° C/ 2.16 Kg)	ASTM D1238/L	gr/10min	8.5
Tear strength(Longitudinal/Transverse)	DIN 53455	MPa	40/36
Elongation at break (Longitu./Trans.)	DIN 53455	%	660/680
Flexural modulus (Longitu./Trans.)	DIN 53121	Mpa	650/630
Dart drop impact strength F50	ASTM D1709	gr	330
Coefficient of sliding friction	DIN 53375	-	0.2
Melting Point , DSC	ASTM D3417	°C	163
Gloss(20°)	ISO 2813	%	120
Haze	ASTM D1003	%	1.9
Density	ASTM D792	gr/cm3	0.91

"The information in this publication is submitted without prejudice, and is based on our current knowledge and experience and on a limited number of tests.

In view of the many factors that may affect processing and application, these data do not relieve the receiver of this information from the responsibility of carrying out their own tests and experiments; neither do they imply and legally binding assurance of certain properties or of suitability for a specific purpose of the products made with or on the basis of the information in this publication."